



DEWALT®



LENOX®



STANLEY®



**CORDLESS TOOLS — FORCIBLE ENTRY & UTILITY BARS — LIGHTING
FIRE & RESCUE RECIPROCATING SAW BLADES — PORTABLE POWER**



55-122 30" Fubar® Forcible Entry Tool

- Forcible entry tool designed by responders for vehicle extrication and extreme demolition
- Board jaw sized specifically for grabbing common dimensional lumber
- Beveled nail slot for pulling and prying nails
- Heat treated and tempered striking face helps prevent chipping
- Carabiner holes for easy attachment of shoulder strap
- Hi-visibility 3M™ Scotchlite™ enhances visibility



55-121 18" Fubar® Forcible Entry Tool



STHT55134 14-1/4" Fubar® Demolition Bar



DCS690 60V MAX* 9" Cut-Off Saw Powered by DeWALT FLEXVOLT®

- The brushless motor provides up to 6,600 RPM, allowing the user to make fast and efficient single pass cuts and scores in concrete, pavers, steel, and rebar.
- Cuts up to 96 pieces of #5 rebar per charge¹
¹(Cut in 4 piece rebar bundles using a DCB609 battery)
- Cuts up to 22 cinderblocks in half per charge²
²(Using a DCB609 battery in standard cored concrete block)
- The Heavy Load Indicator light provides the user with real time power and runtime feedback during demanding applications.
- The Rotatable, 5-Position Guard allows the user to select the approach angle, which provides optimal visibility and accessibility when cutting in tight spaces.
- The Dual-Sided Water Delivery System offers an OSHA Table 1 Complaint solution for dust management when cutting concrete and masonry materials.
- The latched and sealed battery box keeps the battery and terminals protected from harsh jobsite conditions.
- This tool comes Tag Ready™ so users and companies can attach the DeWALT Tag™ and track its location virtually anywhere via the DeWALT Tool Connect™ app.
- The beltless All-Metal Drivetrain provides jobsite durability and efficiency. No belts to change, tension, and maintenance.
- The front handle that can be held in three positions, allowing the saw to be securely held to cut in both horizontal and vertical positions.



DWAFV8918
9" Ceramic Metal Cut-Off Wheel Type 1

DWAFV8900
9" Diamond Cutting Wheel

Maximum initial battery voltage (measured without a workload) is 20, and 60 volts. Nominal voltage is 18 and 54. All amp hours (Ah) shown with 60V MAX products are measured in 20V MAX* mode.

POWER TOOLS

NO GAS, NO CORDS, NO GENERATORS

DEWALT

DCS389

60V MAX* Brushless Reciprocating Saw Powered by DeWALT FLEXVOLT®

- Fast and efficient cutting with up to 3,000 SPM and a 1-1/8" stroke length.
- Illuminate dark work areas with the integrated LED
- More points of contact with pivoting shoe
- Variable Speed Trigger for speed control



RECIPROCATING SAW BLADES

LENOX

WHEN PERFORMANCE MATTERS, TRUST LENOX

GENERAL PURPOSE

10 TPI 9" x 1" x .062" Demolition Reciprocating Saw Blade
 20372960R5 (5 Pack)
 20524B960R (25 Pack)
 22762OSB960R (50 Pack)



³vs. prior generation LENOX straight blades

GOLD® POWER ARC™ METAL CUTTING

10 TPI 9" x 1" x .062" Gold® POWER ARC™ Curved Demolition Reciprocating Saw Blade
 21089960GR (5 Pack)
 21221B960GR (25 Pack)



⁴vs. LENOX straight bi-metal reciprocating saw blades.

LAZER CT™ CARBIDE TIPPED

HIGH PERFORMANCE IN METAL CUTTING

8 TPI LAZER CT™ Carbide Tipped Reciprocating Saw Blades

6" x 1" x .052" 2014223 (5 Pack)
 9" x 1" x .052" 2014225 (5 Pack) UP TO 50X LIFE⁵



⁵vs. 10TPI Standard LENOX Bi-Metal reciprocating saw blades cutting cast iron and rebar.

DEMOLITION CT™ CARBIDE TIPPED

HIGH PERFORMANCE IN WOOD CUTTING

6 TPI DEMOLITION CT™ Carbide Tipped Reciprocating Saw Blades

6" x 1" x .05" 1832162 (5 Pack)
 9" x 1" x .05" 1832144 (5 Pack)
 12" x 1" x .05" 1832147 (5 Pack) UP TO 50X LIFE⁶



⁶vs. 6TPI standard LENOX Bi-Metal reciprocating saw blades cutting wood with nails.



Maximum initial battery voltage (measured without a workload) is 20 and 60 volts. Nominal voltage is 18 and 54. All amp hours (Ah) shown with 60V MAX products are measured in 20V MAX* mode.



POWER TOOLS

NO GAS, NO CORDS, NO GENERATORS

DCG418 60V MAX* Brushless 4-1/2" / 6" Grinder Powered by DeWALT FLEXVOLT®



- Up to 30% more power vs the DCG414[†]
- 13.0 Amp motor equivalent power
- 9000 rpm no-load speed for applications with 6" grinder wheels
- Brake engages when the trigger is released with stopping speeds of 1.5 seconds with standard grinding wheel (4-1/2" x 1/4" Bonded abrasive wheel, non-hubbed)
- Kickback Brake engages when a pinch, stall, or bind-up event is sensed. The electronic brake engages with maximum force to quickly stop the wheel, reduce the movement of the grinder, and shut the grinder off
- E-Clutch® System activates in less than a tenth of a second when a pinch/stall is detected, shutting down the motor



DCCS670 60V MAX* Brushless 16" Chainsaw Powered by DeWALT FLEXVOLT®



- Up to 70 cuts per charge on a 6" x 6" pressure-treated wood using DCB609 Battery
- Tool-Free chain tensioning for quick and smooth adjustments
- Combination tooled/tool less bar retention knob for proper bar clamping force
- Chain brake for kick back protection
- Auto-oiling for continuous lubrication.
- Quarter-turn cap for quick oil refills
- High-efficiency brushless motor maximizing run time and motor life



[†]The DeWalt DCG418 with a DCB609 60V MAX* DeWALT FLEXVOLT™ battery has up to 30% more power vs. DeWalt DCG414 with a DCB606 60V MAX* battery

Maximum initial battery voltage (measured without a workload) is 20 and 60 volts. Nominal voltage is 18 and 54. All amp hours (Ah) shown with 60V MAX products are measured in 20V MAX* mode.

POWER TOOLS

NO GAS, NO CORDS, NO GENERATORS

DeWALT

DCN21PL
20V MAX* XR® Brushless 21° Plastic Collated
Cordless Framing Nailer



NO COMPRESSOR

NO AIR HOSES

DCN692
20V MAX* XR® Brushless
Dual Speed Framing Nailer



NO COMPRESSOR


NO AIR HOSES

CONCRETE DEMOLITION

DCH733
60V MAX* Brushless 1-7/8"
SDS MAX Rotary Hammer
Powered by DeWALT FLEXVOLT®




DWA5851
16" High Impact Bull
Point Steel Chisel



DWA5854
16" High Impact
Scaling Chisel



DWA5853
16" High Impact
Cold Chisel



DCS577
60V MAX* Brushless 7-1/4" Cordless Worm Drive Style
Saw Powered by DeWALT FLEXVOLT®



DCD991
20V MAX* XR® Brushless
3-Speed Drill/Driver



DCS494
20V MAX* 14 Gauge Swivel Head Double Cut Shears



DCS578
60V MAX* Brushless 7-1/4" Circular Saw with Brake
Powered by DeWALT FLEXVOLT®



DCF899H
20V MAX* XR® High Torque
1/2" Impact Wrench with
Hog Ring Anvil



D28605
5/16" Variable Speed Fiber Cement Siding Shear



CORDED

DCBL772
60V MAX* Brushless Handheld Axial Blower Powered by DeWALT FLEXVOLT®



Maximum initial battery voltage (measured without a workload) is 20 and 60 volts. Nominal voltage is 18 and 54. All amp hours (Ah) shown with 60V MAX products are measured in 20V MAX* mode.

DCL043

20V MAX* Jobsite LED Spotlight

- 3 bright LEDs illuminate
- 1 bright Red LED to preserve night vision
- 2 brightness settings provide flexibility for maximum light output or extended run-time
- 90-degree pivoting head
- Pivoting head allows for hands-free operation and light to be projected in multiple directions while standing on its base
- Belt hook to provide increased versatility for transportation and a hands-free use in multiple placements
- Integral hook for hands-free use in multiple placements
- Over-molded lens cover provides increased durability



BRIGHTNESS	1,000 & 90 LUMENS
BULB TYPE	LED
TOOL WEIGHT	1.42 lb WITHOUT BATTERY



DCL074

20V MAX* LED Worklight with Tool Connect™

- LED provides natural white light
- Set up with freestanding, tripod-mounted (sold separately), or hanging via hook
- Durable impact-resistant design
- IP54 rating for weather and dust resistance

BRIGHTNESS	5,000 LUMENS
BULB TYPE	LED
TOOL HEIGHT	12"
TOOL WEIGHT	8.6 lb WITHOUT BATTERY



DCL079

20V MAX* Cordless Tripod Light

- Natural white LED provides accurate color visibility, long life span, and stays cool to the touch
- Three brightness settings to customize work space illumination
- Telescoping pole extends light head to 7 feet to reduce shadows and glare
- Latch mechanism on handle to easily extend and collapse legs
- Tough shroud protects light head
- IP55 rating for weather and dust resistance

BRIGHTNESS	UP TO 3,000 LUMENS
RUN-TIME	UP TO 11 HOURS ⁸
BULB TYPE	LED
TOOL HEIGHT	UP TO 7 FEET
TOOL WEIGHT	16 lb WITHOUT BATTERY

⁸using DCB206 battery on low



PORTABLE POWER

BATTERIES, CHARGERS & ELECTRIC GENERATOR



DCB606
DeWALT FLEXVOLT® 20V MAX*/60V MAX*
Battery Pack (6.0 Ah)



DCB609
DeWALT FLEXVOLT® 20V MAX*/60V MAX*
Battery Pack (9.0 Ah)



DCB612
DeWALT FLEXVOLT® 20V MAX*/60V MAX*
Battery Pack (12.0 Ah)



DCB206
20V MAX* Premium XR® Lithium Ion Battery Pack (6.0 Ah)



DCB208
20V MAX* Premium XR® Lithium Ion Battery Pack (8.0 Ah)



DCB104
Multiport Simultaneous Fast Charger

- Simultaneous Charger: All Ports Charge At The Same Time
- Charges 12V MAX*, 20V MAX*, and DeWALT FLEXVOLT® 20V MAX*/60V MAX* Batteries
- 8.0 Amps Output Per Port (simultaneously)
- Charges (4) DCB204 battery in 40 mins
- Charges (4) DCB606 battery in 60 mins
- Thru-Hole Wall Mounts and Cord Wraps
- Side Brackets To Mount Onto The ToughSystem® Rails



DCB1800
1800 Watt Portable Power Station™ and Simultaneous Battery Charger

NO GAS TO RUN

CHARGING TIME	2 HOURS (4.0 Ah Batteries)	
DIMENSIONS	Height	10.75"
	Width	21.3"
	Length	12.75"
OUTPUT	1800 WATTS (3600 Peak) 15.0 Amps	
OPERATING TEMP	32°–104° F	
TOOL WEIGHT	18 lb WITHOUT BATTERIES	

Batteries and cord sold separately

Charges 4 Batteries Simultaneously
(Batteries and cord sold separately)

Multiport Parallel Charger
when plugged into an Outlet



ToughSystem® Compatible



1800 Watts Continuous 15 Amps
(3600 Peak) from (4) Batteries
Requires 4 batteries to operate

Maximum initial battery voltage (measured without a workload) is 12, 20, and 60 volts. Nominal voltage is 10.8, 18, and 54. All amp hours (Ah) shown with 60V MAX products are measured in 20V MAX* mode.



MAIL-IN REBATE

OFFER VALID DECEMBER 8, 2020 THROUGH MARCH 31, 2021 • WHILE SUPPLIES LAST.
MUST BE POSTMARKED BY APRIL 15, 2021

BUY SELECT DeWALT TOOLS

YOUR CHOICE.

GET A 9.0 Ah DeWALT FLEXVOLT® BATTERY

VIA MAIL-IN REBATE.

I BOUGHT: (CHECK ONE)

<input type="checkbox"/> DCS690X2 60V MAX* 9" Cut-Off Saw Kit Powered by DeWALT FLEXVOLT® (9.0 Ah) (2 Battery Kit)	<input type="checkbox"/> DCS389X1 60V MAX* Brushless Reciprocating Saw Kit Powered by DeWALT FLEXVOLT® (9.0 Ah)	<input type="checkbox"/> DCG418X1 60V MAX* Brushless 4-1/2" / 6" Grinder Kit Powered by DeWALT FLEXVOLT® (9.0 Ah)	<input type="checkbox"/> DCCS670X1 60V MAX* Brushless 16" Chainsaw Kit Powered by DeWALT FLEXVOLT® (9.0 Ah)	<input type="checkbox"/> DCH733X2 60V MAX* 1-7/8" SDS MAX Rotary Hammer Kit Powered by DeWALT FLEXVOLT® (9.0 Ah) (2 Battery Kit)
<input type="checkbox"/> DCN21PLM1 20V MAX* 21° Plastic Collated Cordless Framing Nailer Kit (4.0 Ah)	<input type="checkbox"/> DCN692M1 20V MAX* XR® Brushless Dual Speed Framing Nailer Kit (4.0 Ah)	<input type="checkbox"/> DCS577X1 60V MAX* 7-1/4" Cordless Worm Drive Style Saw Kit Powered by DeWALT FLEXVOLT® (9.0 Ah)	<input type="checkbox"/> DCS575T2 60V MAX* 7-1/4" (184 mm) Circular Saw Kit with Brake Powered by DeWALT FLEXVOLT® (6.0 Ah) (2 Battery Kit)	<input type="checkbox"/> DCBL772X1 60V MAX* Brushless Handheld Axial Blower Kit Powered by DeWALT FLEXVOLT® (9.0 Ah)
<input type="checkbox"/> DCD991P2 20V MAX* XR® Brushless 3-Speed Drill/Driver Kit (5.0 Ah) (2 Battery Kit)	<input type="checkbox"/> DCF899HP2 20V MAX* XR® High Torque 1/2" Impact Wrench with Hog Ring Anvil Kit (5.0 Ah) (2 Battery Kit)	<input type="checkbox"/> DCS494M2 20V MAX* 14 Gauge Swivel Head Double Cut Shears (4.0 Ah) (2 Battery Kit)	<input type="checkbox"/> DCL079R1 20V MAX* Cordless Tripod Light Kit (6.0 Ah)	<input type="checkbox"/> DCL074 20V MAX* LED Worklight with Tool Connect™

I GET:

DCB609
DeWALT FLEXVOLT® 20V MAX*/60V MAX* Battery Pack (9.0 Ah)




All amp hours (Ah) shown with 60V MAX* products are measured in 20V MAX* mode.

Terms and Conditions: Limit of 5 rebate items per customer. This is not a game of chance. Rebate item provided by mail. Mail-In Rebates are valid for qualifying DeWALT products purchased 12/8/2020 through 3/31/2021 from authorized participating Independent Channel retail locations only. All rebate requests must be postmarked by 4/15/2021. Void where prohibited. All federal, state and local laws and regulations apply. DeWALT is not responsible for lost, late, misdirected, or illegible submitted rebate materials. Offer void if original receipt or invoice (except for Rhode Island residents*), UPC Barcode, and completed mail-in-rebate form(s) are not submitted. Program is not available for purchases of factory-reconditioned products. Rebate materials must be obtained legitimately through an authorized participating Independent Channel retailer. DeWALT reserves the right, in their sole discretion, to (i) determine the validity and legitimacy of any rebate materials submitted, and (ii) approve or disapprove the participation of the person in this rebate offer. Fraudulent submissions may result in prosecution, fines, penalties, damages or liability and may be pursued to the fullest extent of the law. All submitted mail-in-rebate materials become the property of DeWALT and will not be returned. Offer valid only for product end users with a U.S.A. street mailing address (cannot ship to a post office box), and is not available to DeWALT distributors or resellers. DeWALT reserves the right, in its sole discretion, to alter, change, terminate, suspend or otherwise cancel this rebate offer at any time for any reason. DeWALT reserves the right to substitute rebate item for one of equal or greater value if any rebate item is unavailable. These terms and conditions are subject to change without notice. Income and other taxes (if any) are the sole responsibility of the participant. Not valid with any other DeWALT offer or promotion. Not Valid for Government Customers. Each participant agrees to release and hold DeWALT, their employees, officers, directors, shareholders, agents, representatives, and its subsidiaries, parent companies and other affiliated companies harmless from any and all damages, losses, claims and/or liabilities arising out of the participant's participation in this rebate offer or resulting from the participant's acceptance or claim of any item hereunder. Rebate items are not redeemable for cash or credit. Residents of Canada are not eligible to participate in this Mail-In Rebate offer. Online purchases are not valid for this Mail-In Rebate offer.

All of the below steps must be completed and purchase must be made at an authorized participating Independent Channel retail location to qualify for this rebate offer.

- Include the following items with your claim: (mail claim in a stamped envelope)
 - Rebate Form** complete in its entirety (please use capital letters)
 - Original sales receipt** or sales invoice (except for RI Residents*) evidencing purchase dated between 12/8/2020 and 3/31/2021 from an authorized participating Independent Channel retail location (please make a copy of your receipt or invoice for your own records)
 - Original UPC Barcode** from the purchased qualifying DeWALT products.
- Please send my rebate item to:



First Name	Last Name	MI
Street Address (cannot ship to a Post Office box)		
City	State	Zip Code
Phone Number	Email Address	

- Participant also acknowledges that purchases made and submitted in connection with this offer are not redeemable for cash or credit and cannot be combined with any other rebate, offer or other promotion, regardless of whether offered by a DeWALT authorized retailer.
- Participant hereby acknowledges that the information provided herein is true and accurate in all material respects.

5. Did you remember to include the following?

- ☐ A completed Rebate Form for each rebate request
- ☐ Original Independent Channel sales receipt or sales invoice (except for RI Residents*) evidencing qualifying purchase
- ☐ Original UPC Barcode from the product's packaging

- In a stamped envelope, mail original sales receipt or invoice (except for RI Residents*) evidencing purchase, original UPC barcode and completed mail-in rebate form to:

DeWALT
DWMY043
PO Box 42833
Towson, MD 21284

To check the status of your rebate call 866-444-5290
Please allow 5-7 weeks for delivery.

* A photocopy is permitted for Rhode Island residents.

- ☐ 3. I would like to receive e-mails from DeWALT regarding new products and special offers. Please refer to DeWALT's privacy policy on www.DeWALT.com. I agree to and understand that I can unsubscribe at any time.

Maximum initial battery voltage (measured without a workload) is 12, 20, and 60 volts. Nominal voltage is 10.8, 18, and 54. All amp hours (Ah) shown with 60V MAX products are measured in 20V MAX* mode.

Copyright © 2020 Stanley Black & Decker, Inc. The following are trademarks for one or more DeWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.
ICD/LXSTFRBR Dec-Mar MIR Brochure 120220.Indd/RO/GDS/20-1811166